Clean N' Shine 2X is formulated to be the most powerful, neutral, all purpose cleaner/degreaser for use on any water washable surface. Safe for use on painted surfaces, most plastics, all metals, sealed wood, and resilient and non-resilient flooring. Excellent for removal of even the toughest greases and soils, rinses free to provide a sparkling clean surface.

FEATURES

- For soil removal in areas where a neutral cleaner isn't strong enough — finished floors, walls, painted wood, concrete floors, plastic and other water-safe surfaces.
- Removes hard water deposits, stripper residue as well as particulate soil like sand and grit.
- Concentrated for economy

GLEAN N' SHINE 2X

> Low foam formula makes it ideal for autoscrubbers or buckets.

All Purpose

Cleaner

NEUTRAL PH CLEANER

FOR ALL WASHABLE SURFACES

Concentrated Formula

· Meets ASTM D2047 method for slip resistance

PROPERTIES_

Туре	Synthetic Detergent
Form	Clear Liquid
Odor	Citrus
Color	Red
Weight per Gallon	8.53 Lbs.
рН	

ph 1%	9.7 - 11.7
Storage Stability	Min. 1 Year
Freeze/Thaw	Passes 3 Cycles
Foam Height	Low
Actives	> 15%
*See product label and MSDS for complete	use and safety information.





DIRECTIONS

Formulated to be the most powerful, neutral, all purpose cleaner/degreaser for use on any water washable surface. Safe for use on painted surfaces, most plastics, all metals, sealed wood, and resilient and non-resilient flooring. Excellent for removal of even the toughest greases and soils, rinses free to provide a sparkling clean surface.

General Cleaning and Degreasing: Using the chart below, dilute the product with hot or cold water (use only cold water on finished floors) and apply by any convenient method. Allow a few moments to work, then rinse and allow to dry.

Light Duty General Purpose	3 - 5 oz. per gallon*	
General Cleaning	6 - 8 oz. per gallon	
Heavy Duty General Cleaning	9 - 11 oz. per gallon	
Degreasing & Soak Tank Cleaning12 - 14 oz. per gallon		
*No rinsing required		

Specialty Operations:

Ultrasonic Cleaners: 10 oz./gal.

Aluminum Trucks, Aircraft, General Automotive Applications: 64 oz./gal.

Food Plants and Industrial Applications: 20 oz./gal.

DISPOSAL: PRODUCT: Dispose of excess product in accordance with local, state and federal regulations. **CONTAINER:** Please recycle HDPE container.

VENTILATION: No special is ventilation needed. However, use of adequate ventilation is good industrial practice.

IMPROPER USE OR DILTION:

IMPROPER USE: May irritate eyes, skin, gastrointestinal and respiratory tracts. May be absorbed through skin with prolonged or repeated contact. Avoid eye and skin contact.

IMPROPER DILUTION: Over dilution will lead to a film buildup. Under dilution may cause performance problems.

FIRST AID: EYES & SKIN: Flush with water (eyes 15 minutes). **INGESTION:** If swallowed, give 2-3 large glasses of water. Seek medical attention. In all cases if symptoms persist, seek medical attention.



3700 Reveille • Houston, TX 77087 • 713-649-4121