



# LIGHTNING STRIP

## Floor Finish Remover

This professional strength stripper is our most powerful stripper. Lightning Strip is designed to cut through heavy finish buildup fast. And, its low foam formula is perfect for application with auto-scrubbers.

*Heavy-Duty,  
Contractor-Grade*

**REMOVES HEAVY  
BUILD-UP**



## FEATURES

- Low odor, slow evaporation formula
- Contractor-grade formulation strips hard to remove finishes and seals
- Eliminates or greatly reduces machine scrubbing
- Powerful enough to remove multiple layers, build-up or highly burnished finish
- Low foam for easy application with automatic-scrubbers
- Designed to strip equally well in cold or warm water

## PROPERTIES

|                         |                        |  |                 |
|-------------------------|------------------------|--|-----------------|
| Type .....              | Solvent/Amine Stripper | Storage Stability .....  | Min. 1 Year     |
| Form .....              | Clear Liquid           | Freeze/Thaw .....  | Passes 3 Cycles |
| Odor .....              | Mild Solvent           | Foam Height .....  | Very Low        |
| Color .....             | Light Blue             | Actives .....  | >25%            |
| Weight per Gallon ..... | 8.52 Lbs.              | Phosphate (%P) .....   | None            |
| pH .....                | 13.2                   | *See product label and MSDS for complete use and safety information. |                 |
| pH @ 1:4 .....          | 12.3                   |  |                 |





# LIGHTNING STRIP

## PRODUCT SAFETY AND TRAINING

### DIRECTIONS

#### READ BEFORE USING

1. This is a highly aggressive formula. Read precautions below.
2. Dilute before using. DO NOT use on painted surfaces or wooden floors. Test for softening or color bleeding before stripping linoleum, rubber or asphalt tile as stripper may cause bleaching, softening, or bleeding.
3. Rinse immediately with water and pick up. Wipe up any spills or splashes from baseboards or painted surfaces.  
**NOTE:** For stripping or maintaining asbestos-containing tile, follow OSHA or EPA guidelines.
4. Use in well ventilated area.

#### DIRECTIONS FOR USE:

1. Dust mop floor.
2. To remove heavy build-up, dilute 1 part Lightning Strip with 4 parts water (32 oz./gal).
3. Before applying to entire floor, test on a small, inconspicuous area.
4. Apply a liberal amount of solution to floor area. Permit solution to remain on floor for 3-5 minutes. Do not allow solution to dry on floor.
5. Scrub thoroughly with machine and stripping pad. Then pick up solution.
6. Rinse well with clear water. Recommended two rinses with neutral cleaner in last rinse.
7. Allow floor to dry before applying finish.

**DISPOSAL: PRODUCT:** Dispose of excess product in accordance with local, state and federal regulations.

**CONTAINER:** Please recycle HDPE container.

**VENTILATION:** No special is ventilation needed. However, use of adequate ventilation is good industrial practice.

### IMPROPER USE OR DILUTION

**IMPROPER USE: CORROSIVE LIQUID.** May cause severe eye, skin and gastrointestinal irritation or burns. May be absorbed through skin with prolonged or repeated contact. Use in poorly ventilated area may cause respiratory irritation. Avoid contact with eyes, skin and clothing. Use with adequate ventilation.

**IMPROPER DILUTION:** Over dilution reduces stripper efficacy.

### FIRST AID

**EYES & SKIN:** Flush with water for 30 minutes. **INGESTION:** If swallowed, give 2-3 large glasses of water. DO NOT induce vomiting. Seek medical attention. **INHALATION:** Remove to fresh air and rest. In all cases if symptoms persist, seek medical attention.