



SUPER BLUE Floor Cleaner

**Heavy-Duty,
No-Rinse Cleaner**

**GREAT FOR
ALL WASHABLE
SURFACES**

Super Blue is a phosphate-free all-purpose cleaner that is concentrated for economy. It's a synthetic detergent that contains no free alkali so it rinses without leaving a residue. Excellent for removal of salt and ice-melting residues. Use it on resilient tile, concrete and terrazzo floors. Also excellent for walls, woodwork and equipment.



FEATURES

- Mild pH (9.1 in dilution) – great for cleaning heavily soiled finished floors
- Free-rinsing, non-dulling, and low foam all surface cleaner
- Variable dilution – from 1-8 ounces per gallon
- Neutralizes ice melter residue prior to recoating
- Removes soap scum from walls, sinks, tubs, etc.
- Meets ASTM D2047 method for slip resistance

PROPERTIES

Type	Synthetic Detergent	pH 1%	9.1
Form	Clear Liquid	Storage Stability	Min. 1 Year
Odor	Citrus	Freeze/Thaw	Passes 3 Cycles
Color	Blue	Foam Height	Very Low
Weight per Gallon	8.69 Lbs.	Actives	> 15%
pH	11.6 - 12.7	*See product label and MSDS for complete use and safety information.	





SUPER BLUE

PRODUCT SAFETY AND TRAINING

DIRECTIONS

For complete maintenance of all washable surfaces. A chemically balanced detergent containing nonionic surfactant, emulsifier, and sequestering agent for finest all around cleaning. Follow the recommended dilutions below. Smaller amounts can be used for light duty cleaning. Directions are based on adverse conditions.

For use on all linoleum, rubber, asphalt, synthetic, vinyl, granite, terrazzo, hard tile, concrete, sealed wood and any washable surface. Do not use on marble.

DAMP MOPPING: 1 part concentrate to 128 parts water (1 ounce per gallon).

GENERAL CLEANING: 1 part concentrate to 64 parts water (2 ounces per gallon).

AFTER STRIP NEUTRALIZING: 1 ounce per gallon.

EXTREME SOIL: 1 part concentrate to 20 parts water (6 ounces per gallon).

SCRUBBING MACHINES: Generally 1 pint to 1 quart per 16 gallon tank with water depending on soil conditions.

ALSO EXCELLENT FOR

AUTOMOBILES: For hand cleaning: 1 ounce per gallon. Pressure wash ¼ ounce per gallon.

ALUMINUM – STAINLESS STEEL: Dilute 1 to 40 with warm water (3 ounces per gallon). Apply with clean cloth, agitate lightly. Wipe with damp cloth, then dry with clean, dry cloth.

DISPOSAL: PRODUCT: Dispose of excess product in accordance with local, state and federal regulations.

CONTAINER: Please recycle HDPE container.

VENTILATION: No special is ventilation needed. However, use of adequate ventilation is good industrial practice.

IMPROPER USE OR DILUTION:

IMPROPER USE: May irritate eyes, skin and gastrointestinal tract. Avoid eye and skin contact.

IMPROPER DILUTION: Over dilution will lead to a film buildup. Under dilution may cause performance problems.

FIRST AID: EYES & SKIN: Flush with water (eyes 15 minutes). **INGESTION:** If swallowed, give 2-3 large glasses of water. Seek medical attention. In all cases if symptoms persist, seek medical attention.

FURNITURE AND WOODWORK: Dilute 1 part to 60 parts water. Wipe with damp cloth, then dry with clean dry cloth.

GLASS: Dilute 1 ounce per gallon of water. Spray on, wipe off.

GYM FLOORS: Dilute 1 part to 15 parts hot water, let stand and scrub as necessary. For scuffs or stains on baseboards, use steel wool with solution and rub lightly.

LEATHER – PLASTIC UPHOLSTERY: Dilute 1 to 60 with water. Apply with spray, cloth or sponge, wipe dry.

TRUCKS – AIRCRAFT: Dilute 1 to 30 with water, apply with brush and hose off.

FOR FOOD PLANT USE: Food contact surfaces are to be rinsed with potable water before reuse.

NOTE: For stripping and maintaining asbestos containing tile, follow OSHA guidelines or EPA guidelines.