



XTREME STRIP

Finish Remover

Ultra-Concentrated

**VERY LOW ODOR
REMOVES HEAVY
BUILD-UP**

Xtreme Strip is an ultra-concentrated, high-productivity stripper. It is over 80% active and is designed to quickly attack and liquefy heavily recoated and burnished floors. Ultra activity usually means a long dilution ratio and Xtreme Strip doesn't disappoint with its 1:19 dilution. You and your customers will also appreciate the low odor profile.

FEATURES

- Ultra-concentrated 1:19 dilution provides the utmost in economy and convenience and greatly reduces inventory
- Powerful enough to remove multiple layers of highly burnished finishes
- Aggressive dual-solvent formulation easily strips all seals and finishes on the first pass
- Effective in cold to warm water
- LOW ODOR formulation affords user comfort and eliminates complaints

PROPERTIES

Type	High Active Stripper	Storage Stability	Min. 1 Year
Form	Clear Liquid	Freeze/Thaw	Passes 3 Cycles
Odor	Slight Solvent	Foam Height	Moderate
Color	Aqua	Actives	> 80%
Weight per Gallon	8.47	Phosphate (%P)	None
pH	10.5 - 11.5	*See product label and MSDS for complete use and safety information.	
pH 1%	10.5		





XTREME STRIP

PRODUCT SAFETY AND TRAINING

DIRECTIONS

READ BEFORE USING

1. This is a highly aggressive formula. Read precautions below.
2. Dilute before using. Do not use on painted surfaces or wooden floors. Use cautiously for stripping linoleum, rubber or asphalt tile as stripper may cause bleaching softening or bleeding.
3. Wipe up any spills or splashing from baseboards or painted surfaces immediately.

DIRECTIONS

1. To remove heavy build-up, dilute with warm water as follows:
1 part stripper to 19 parts water. DO NOT use at other dilution ratios.
2. Apply liberally to floor covering 100 square feet at a time. Be sure to leave surface VERY wet!
3. Allow to remain on floor 3 to 5 minutes. Agitate for 100% removal of old floor finish.
4. Pick up solution using a wet vac or auto-scrubber. If any finish remains (around baseboards), reapply stripping solution and agitate as necessary.
5. Rinse floor thoroughly. Recommended two rinses with neutral cleaner in last rinse. Allow floor to dry.
6. Apply finish or seal.

NOTE: For stripping and maintaining asbestos containing tile, follow OSHA or EPA guidelines.

DISPOSAL: PRODUCT: Dispose of excess product in accordance with local, state and federal regulations.

CONTAINER: Please recycle HDPE container.

VENTILATION: No special is ventilation needed. However, use of adequate ventilation is good industrial practice.

IMPROPER USE OR DILUTION

IMPROPER USE: CORROSIVE LIQUID. May cause severe eye, skin and gastrointestinal irritation or burns. May be absorbed through skin with prolonged or repeated contact. Use in poorly ventilated area may cause respiratory irritation. Avoid contact with eyes, skin and clothing. Use with adequate ventilation.

IMPROPER DILUTION: Over dilution reduces stripper efficacy. Always add at least 19 parts water to Xtreme Strip.

FIRST AID

EYES & SKIN: Flush with water for 30 minutes. **INGESTION:** If swallowed, give 2-3 large glasses of water. DO NOT induce vomiting. Seek medical attention. **INHALATION:** Remove to fresh air and rest. In all cases if symptoms persist, seek medical attention.